

By Category PDF

Category Sensors & MEMS

ICs

Sensors & MEMS

Hall ICs	80
Omnipolar Detection Hall IC	80
Omnipolar Detection Hall ICs with Polarity Discrimination (Polarity Detection for Both S and N Features Dual Outputs)	80
Industrial Equipment Latch Type Hall IC	80
Automotive Unipolar Hall ICs	80
Automotive Latch Type Hall ICs	80
Geomagnetic Sensor IC	81
3-Axis Digital Magnetometer IC	81
Current Sensor ICs	81
Contactless Current Sensor IC	81
Current Sense Amplifier IC	81
Ambient Light Sensor ICs	81
Analog Current Output type Ambient Light Sensor ICs	81
Digital 16bit Serial Output type Ambient Light Sensor ICs	81
Color Sensor IC	81
Digital 16bit Serial Output type Color Sensor IC	81
Pressure Sensor IC	82
Digital Pressure Sensor ICs with Built-in Temperature Compensation Function	82
Temperature Sensor ICs	82
Analog Output Temperature Sensor IC	82
Digital Output Temperature Sensor IC	82
Shock Sensor Amplifier	82
Shock Sensor Amplifier	82
Accelerometers	82
3-Axis Accelerometers	82

Sensors & MEMS

Hall ICs	P.80	Geomagnetic Sensor IC	P.81
Current Sensor ICs	P.81	Ambient Light Sensor ICs	P.81
Color Sensor IC	P.81	Pressure Sensor IC	P.82
Temperature Sensor ICs	P.82	Shock Sensor Amplifier	P.82
Accelerometers	P.82		

Click on the icon to access the product page on ROHM's website. Please check the website for the latest updates.

Hall ICs

Omnipolar Detection Hall IC Detects S- or N-pole Magnetic Fields and Turns the Output ON (active Low)

Part No.	Supply Voltage (V)	Operate Point (mT)		Pulse Drive Period (ms)	Supply Current (Avg.) (μA)	Output	Operating Temperature (°C)	Package
		S-pole	N-pole					
BD7411G	4.5 to 5.5	+3.4	-3.4	—	2.0 (mA)	CMOS	-40 to +85	SSOP5

Omnipolar Detection Hall ICs with Polarity Discrimination (Polarity Detection for Both S and N Features Dual Outputs) Features 2 Outputs to Discriminate Between N- and S-pole Detection

Part No.	Supply Voltage (V)	Operate Point (mT)		Pulse Drive Period (ms)	Supply Current (Avg.) (μA)	Output	Operating Temperature (°C)	Package (mm)
		S-pole	N-pole					
BU52272NUZ	1.65 to 3.60	+2.4	-2.4	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	VSON04Z1114A 1.1x1.4, H=Max 0.4
BU52072GWZ	1.65 to 3.60	+2.4	-2.4	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52073GWZ	1.65 to 3.60	+4.1	-4.1	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52074GWZ	1.65 to 3.60	+6.3	-6.3	50	4.4	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52075GWZ	1.65 to 3.60	+9.5	-9.5	50	5.0	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52737GWZ	2.5 to 4.5	+15.0	+15.0	50	0.8	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52077GWZ	1.65 to 3.60	+15.0	-15.0	50	5.0	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4
BU52078GWZ	1.65 to 3.60	+24.0	-24.0	50	5.0	CMOS (2 Outputs: S, N pole)	-40 to +85	UCSP35L1 0.8x0.8, H=Max 0.4

Industrial Equipment Latch Type Hall IC

Part No.	Supply Voltage (V)	Operate Point (mT)		Magnetic Signal Input Frequency (Hz)	Supply Current (μA)	Output	Operating Temperature (°C)	Package (mm)
		S-pole	N-pole					
New BD54132G-LBZ	2.5 to 38	2.7	-2.7	20k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12

Automotive Unipolar Hall ICs

Part No.	Supply Voltage (V)	Operate Point (mT)		Magnetic Signal Input Frequency (Hz)	Supply Current (μA)	Output	Operating Temperature (°C)	Package (mm)	Automotive Grade AEC-Q100
		S-pole	N-pole						
BD53103G-CZ	2.7 to 38	3.5	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53104G-CZ	2.7 to 38	7.5	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53105G-CZ	2.7 to 38	10.0	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53106G-CZ	2.7 to 38	12.5	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53107G-CZ	2.7 to 38	18.0	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD53108G-CZ	2.7 to 38	28.0	—	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES

Automotive Latch Type Hall ICs

Part No.	Supply Voltage (V)	Operate/Release Point (mT)		Magnetic Signal Input Frequency (Hz)	Supply Current (μA)	Output	Operating Temperature (°C)	Package (mm)	Automotive Grade AEC-Q100
		Bop	Brp						
BD54102G-CZ	2.7 to 38	2.0	-2.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54103G-CZ	2.7 to 38	5.0	-5.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54104G-CZ	2.7 to 38	7.5	-7.5	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54105G-CZ	2.7 to 38	10.0	-10.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES
BD54107G-CZ	2.7 to 38	15.0	-15.0	10k	1.3	Nch Open Drain	-40 to +150	SSOP3A 2.92x2.4, H=Max 1.12	YES

Geomagnetic Sensor IC

3-Axis Digital Magnetometer IC

Part No.	Supply Voltage (V)	Magnetic Measurement (μ T)	Magnetic Sensitivity (μ T/LSB)	Current Consumption (μ A)	I/F	Operating Temperature ($^{\circ}$ C)	Package (mm)
BM1423GMV	1.7 to 3.6	\pm 1,200	0.042	150	I ² C	-40 to +85	MLGA010V020A 2.0x2.0, H=Max 1.0

Current Sensor ICs

Contactless Current Sensor IC

Part No.	Supply Voltage (V)	Magnetic Measurement (μ T)	Magnetic Sensitivity (μ T/LSB)	Current Consumption (μ A)	I/F	Operating Temperature ($^{\circ}$ C)	Package (mm)
BM14270AMUV-LB	2.7 to 5.5	\pm 280	0.045	70	I ² C	-40 to +125	VQFN20QV3535 3.5x3.5, H=Max 1.0

Current Sense Amplifier ICs

Part No.	Ch	Supply Voltage (V)	Quiescent Current (μ A)	Common Mode Voltage (V)	Gain (V/V)	Gain Accuracy (%)	Operating Temperature ($^{\circ}$ C)	Package (mm)
BD14210G-LA	1	2.7 to 5.5	170	-0.2 to +26	20	\pm 1 (Max)	-40 to +125	SSOP6 2.9x2.8, H=Max 1.25
New BD14211G-LA	1	2.7 to 5.5	170	-0.2 to +26	50	\pm 1 (Max)	-40 to +125	SSOP6 2.9x2.8, H=Max 1.25
New BD14215FVJ-LA	2	2.7 to 5.5	310	-0.2 to +26	20	\pm 1 (Max)	-40 to +125	TSSOP-B8J 3.0x4.9, H=Max 1.10

Ambient Light Sensor ICs

Analog Current Output type Ambient Light Sensor ICs

Part No.	Supply Voltage (V)	Sensitivity Variations (%)	Detection Range (lx)	Sensitivity (μ A/lx)	IR Cut	I/F	Operating Temperature ($^{\circ}$ C)	Package
BH1603FVC	2.4 to 5.5	\pm 15	0 to 100,000	0.6	-	Linear Current Output (Source)	-40 to +85	WSOF6
BH1620FVC	2.4 to 5.5	\pm 15	0 to 100,000	0.6	-	Linear Current Output (Source)	-40 to +85	WSOF5
BH1680FVC	2.4 to 5.5	\pm 15	0 to 50,000	6	✓	Linear Current Output (Source)	-40 to +85	WSOF5
BH1682FVC	2.3 to 5.5	\pm 3 μ A	1 to 55,000	-	✓	Logarithmic Current Output (Source)	-40 to +85	WSOF5

Digital 16bit Serial Output type Ambient Light Sensor ICs

Part No.	Supply Voltage (V)	Sensitivity Variations (%)	Detection Range (lx)	Sensitivity (at 100ms) (μ A/lx)	IR Cut	I/F	Operating Temperature ($^{\circ}$ C)	Package
BH1721FVC	2.4 to 3.6	\pm 15	0 to 65,000	1	-	I ² C	-40 to +85	WSOF5
BH1730FVC	2.4 to 3.6	\pm 15	0 to 65,000	0.007	-	I ² C	-40 to +85	WSOF6
BU27034ANUC	1.7 to 2.0	\pm 15	0 to 20,000	0.000016	✓	I ² C	-40 to +85	WSON008X2120

Color Sensor IC

Digital 16bit Serial Output type Color Sensor IC

Part No.	Supply Voltage (V)	λ_p (nm)				Illuminance Measurement (lx)	High Sensitivity	IR Cut	Flicker detection	I/F	Operating Temperature ($^{\circ}$ C)	Package (mm)
		Red	Green	Blue	IR							
BU27006MUC-Z	1.7 to 3.6	630	540	460	825	0 to 50,000	✓	✓	✓	I ² C	-40 to +85	WQFN12X2520A 2.5x2.0, H=Max 0.55

Pressure Sensor IC

Digital Pressure Sensor ICs with Built-in Temperature Compensation Function

Part No.	Supply Voltage (V)	Pressure Range (hPa)	Relative Pressure Accuracy (hPa)	Absolute Pressure Accuracy (hPa)	I/F	Operating Temperature (°C)	Waterproof	Package (mm)
BM1390GLV-Z	1.7 to 3.6	300 to 1,300	±0.06	±1	I ² C	-40 to +85	✓	RLGA10VG020T 2.0x2.0, H=Max 1.0

Temperature Sensor ICs

Analog Output Temperature Sensor IC

Part No.	Supply Voltage (V)	Temperature Accuracy (°C)		Temperature Sensitivity (mV/°C)	Output Voltage (V) (T _s =+30°C, V _{DD} =3V)	Supply Current (μA)	Operating Temperature (°C)	Package
		T _s =+30°C	T _s =-30, +100°C					
BD1020HFV	2.4 to 5.5	±1.5	±2.5	-8.2	1.3	4.0	-30 to +100	HVSOF5

Digital Output Temperature Sensor IC

Part No.	Supply Voltage (V)	Temperature Accuracy (°C) T _s =-20 to +85°C	Current Consumption (μA)	I/F	Operating Temperature (°C)	Package
BH1900NUX	2.7 to 3.6	±3	75	I ² C	-30 to +95	VSON008X2030

Shock Sensor Amplifier

Shock Sensor Amplifier

Part No.	Supply Voltage (V)	Current Consumption (mA)	Notch Frequency (kHz)	Notch Attenuation Rate (dB)	Operating Temperature (°C)	Package
BD3852MUZ-Z	1.6 to 2.3	1.6 to 4.5	31.0	-23.0	-40 to +85	VQFN16Z3030A

Accelerometers

3-Axis Accelerometers

Part No.	Acceleration Range (±g)	Mechanical Signal Bandwidth (Hz)	I/F	Operating Temperature (°C)	Size, No. of Pins, Package	Features
New KX022ACR-Z	2, 4, 8, 16	800	I ² C/SPI	-40 to +85	2x2x1mm, 12pin, LGA	Wake-up and Back-to-sleep Function, 86sets (8bit) or 43sets (16bit) Buffer
New KX132ACR-LBZ	2, 4, 8, 16	4,200 (XY) 2,900 (Z)	I ² C/SPI	-40 to +105	2x2x1mm, 12pin, LGA	Up to +105°C Operating Temperature, Up to 25.6kHz Output Data Rate, 86sets (8bit) or 43sets (16bit) Buffer
New KX134ACR-LBZ	8, 16, 32, 64	8,200 (X) 8,500 (Y) 5,600 (Z)	I ² C/SPI	-40 to +105	2x2x1mm, 12pin, LGA	Up to +105°C Operating Temperature, Up to 25.6kHz Output Data Rate, Wide Mechanical Signal Bandwidth, 86sets (8bit) or 43sets (16bit) Buffer