

# Reliability Test Result

TEST ITEM	1. TEST RESULT					
280±5°C, 109ec, Reflow method 3times   22			CONDITION	STANDARD		
245±5°C Jase., Reflew method  245±5°C Jase., Solder-bath  JESD22-B102  22  0  Imprerature cycle  -55±5°C —150±5°C 200cycles  JESD22-A104  22  0  -55±5°C —150±5°C 200cycles  JESD22-A101  22  0  -65±5°C Jase., Reflew method  JESD22-A104  22  0  -75±5°C —150±5°C 200cycles  JESD22-A101  22  0  -75±5°C —150±5°C 200cycles  JESD22-A101  22  0  -75±5°C —150±5°C 200cycles  JESD22-A102  22  0  -75±5°C —150±5°C 200cycles  JESD22-A102  22  0  -75±5°C —150±5°C 200cycles  JESD22-A108  22  0  -75±5°C —150±5°C 200		260±5°C , 30sec. , Reflow met	260±5°C , 30sec. , Reflow method 3times			
245±5°C ,3sec., Reflow method	Soldering heat resistance	260±5°C , 10sec. , Solder-batt	260±5℃ , 10sec. , Solder~bath		22	0
245±5°C   3sec   Solder-bath   JESD22-B102   22   0		350±10°C , 3sec. , Hand solde	350±10°C , 3sec. , Hand soldering		22	0
245±5°C , 3sec. , Solder-bath  JESD22-B102  22  0  Temperature cycle  -58±5°C → 150±5°C 200cycles  JESD22-A104  22  0  dight temp. high humidity reverse bias  B5±2°C , 85±596RM, specified bias , 1000hours  JESD22-A101  22  0  dight temp. high humidity reverse bias  B5±2°C , 85±596RM, specified bias , 1000hours  JESD22-A102  22  0  dight temperature reverse bias  Tj max., specified bias , 1000hours  JESD22-A102  22  0  dight temperature gate bias  Tj max., specified bias , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. VGSS(max) , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. VGSS(max) , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. VGSS(max) , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. VGSS(max) , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. VGSS(max) , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. VGSS(max) , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. Specified bias , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. Specified bias , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. Specified bias , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. Specified bias , 1000hours  JESD22-A108  22  0  dight temperature gate bias  Tj max. Specified bias , 1000hours  JESD22-A108  22  0  dight temperature gate bias dight temperatur	Saldarability	245±5°C ,3sec. , Reflow meth	245±5°C ,3sec. , Reflow method		22	0
High temp. high humidity reverse bias   85±2°C, 85±596RH, specified bias ,1000hours   JESD22-A101   22   0     Pressure cooker test   121±2°C , 10094RH , 203kPa , 100hours   JESD22-A102   22   0     High temperature reverse bias   Tj max. specified bias , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj max. VGSS(max) , 1000hours   JESD22-A108   22   0     High temperature gate bias   Tj	Solderability	245±5°C , 3sec. , Solder−bath	245±5°C , 3sec. , Solder-bath		22	0
Pressure cooker test    121±2°C , 10096RH , 203kPa , 100hours   JESD22-A102   22   0	Temperature cycle	-55±5°C←→150±5°C 200c	-55±5°C←→150±5°C 200cycles		22	0
High temperature reverse bias  Tj max., specified bias., 1000hours  JESD22–A108  22  0  Itigh temperature gate bias  Tj max, VGSS(max), 1000hours  JESD22–A108  22  0  Itigh temperature gate bias  Tj max, VGSS(max), 1000hours  JESD22–A108  22  0  Itigh temperature gate bias  Tj max, VGSS(max), 1000hours  JESD22–A108  22  0  Itigh temperature gate bias  Tj max, VGSS(max), 1000hours  JESD22–A108  22  0  Itigh temperature gate bias  Tj max, VGSS(max), 1000hours  JESD22–A108  22  0  Itigh temperature gate bias  Tj max, VGSS(max), 1000hours  JESD22–A108  22  0  Itigh temperature gate bias  JESD22–A108  Itigh temperature gate bias  JESD22–A108  Itigh temperature gate bias  Itigh gate gate gate gate gate gate gate gate	High temp. high humidity reverse	e bias 85±2°C, 85±5%RH, specified	85±2°C, 85±5%RH, specified bias ,1000hours		22	0
Tight temperature gate bias  Tight max, VGSS(max), 1000hours  Tight temperature gate bias  Tight max, VGSS(max), 1000hours  Tight max, VGSS(max, 1000hours)  Tight max, VGSS(max), 1000hours  Tight max, VGSS(max, 1000hours)  Tight max, VGSS(max, 1000hours)  Tight max, VGSS(max, 1000hours)  Tight m	Pressure cooker test	121±2℃,100%RH,203kPa,	121±2°C , 100%RH , 203kPa , 100hours		22	0
Ta=25±5°C, ∠Tj≥100°C, ON 120s/OFF 120s per cycle Duration: 15000cycles  Ta=-40(+0/-10)°C ~+85(+10/-0)°C, ON 300s/OFF 300s per cycle Duration: 6000cycles  Lead strength (lead pull)  Sample body fixed, pulling lead axis direction , 2.5N , 10±1sec.  JESD22 A=105  Lead strength (lead pull)  Sample body fixed, pulling lead axis direction , 2.5N , 10±1sec.  JETTA ED-4701/400 Test Method 401  22  0  Z. MEASUREMENT ITEM & CRITERIA  TIEM  CONDITION  Cutoff current : ICBO  Per specification  Cutoff current : IEBO  Per specification  Cutoff current : IEBO  Per specification  Cutoff current gain : hFE  Per specification  Physical  Visual check  Reflow Soldering  Immersed surfase, other than the end of pin as cut-surface, must be covered by solder.	High temperature reverse bias	Tj max., specified bias , 1000hc	Tj max., specified bias , 1000hours		22	0
Intermittent Operation Life Intermittent Operation Life ON 120s/OFF 120s per cycle Duration: 15000cycles  Ta = -40(+0/-10)°C ~+85(+10/-0)°C, ON 300s/OFF 300s per cycle Duration: 6000cycles  Lead strength (lead pull)  Sample body fixed, pulling lead axis direction , 2.5N , 10±1sec.  JEITA ED-4701/400 Test Method 401  22  0  Z. MEASUREMENT ITEM & CRITERIA  ITEM  CONDITION  CRITERIA  Cutoff current : ICBO Per specification Cutoff current : IEBO Per specification  Cutoff current in hFE Per specification  Physical  Visual check  Reflow Soldering  Immersed surfase, other than the end of pin as cut-surface, must be covered by solder.	High temperature gate bias	Tj max, VGSS(max), , 1000hour	Tj max, VGSS(max), , 1000hours		22	0
2. MEASUREMENT ITEM & CRITERIA  ITEM  CONDITION  CRITERIA  Cutoff current : ICBO  Per specification  Cutoff current gain : hFE  Per specification  Physical  Visual check  No outstanding change in physical.  Reflow Soldering  Immersed surfase, other than the end of pin as cut-surface, must be covered by solder.	Intermittent Operation Life or Power and Temperature Cycle	ON 120s/OFF 120s per cycle Duration: 15000cycles Ta=-40(+0/-10)°C ~+85(+10 ON 300s/OFF 300s per cycle	ON 120s/OFF 120s per cycle Duration: 15000cycles  Ta=-40(+0/-10)°C ~+85(+10/-0)°C, ON 300s/OFF 300s per cycle		22	0
TIEM CONDITION CRITERIA  Cutoff current : ICBO Per specification Cutoff current : IEBO Per specification Cutoff current : IEBO Per specification Cutoff current gain : hFE Per specification Cutoff current : IEBO Per specification Cutof	Lead strength (lead pull)	Sample body fixed, pulling lead	Sample body fixed, pulling lead axis direction , 2.5N , 10±1sec.		22	0
TIEM CONDITION CRITERIA  Cutoff current : ICBO Per specification Cutoff current : IEBO Per specification Cutoff current : IEBO Per specification Cutoff current gain : hFE Per specification Cutoff current : IEBO Per specification Cutof		•				
Cutoff current : ICBO Per specification Cutoff current : IEBO Per specification Cutoff			COITEDIA			
Cutoff current : IEBO Per specification According to the electrical characteristics specified by the specification  OC current gain : hFE Per specification  Physical Visual check No outstanding change in physical.  Reflow Soldering Immersed surfase, other than the end of pin as cut-surface, must be covered by solder.		<b>-</b>				
OC current gain : hFE Per specification  Physical Visual check No outstanding change in physical.  Reflow Soldering Immersed surfase, other than the end of pin as cut-surface, must be covered by solder.						
Physical Visual check No outstanding change in physical.  Reflow Soldering Immersed surfase, other than the end of pin as cut-surface, must be covered by solder.	DC current gain : hFE		The same of the same state of the specification			
Solderability  Visual check  must be covered by solder.	Physical	·	Visual check No outstanding change in physical.			
Solder-bath More than 95% of the electrode must be covered with solder.	Solderability	Visual check	Reflow Soldering			
			Solder-bath	More than 95% of the electrode must be covered with solder.		

### 3. JUDGEMENT

No failure is observed from each test item.

#### Notes

- 1) The information contained herein is subject to change without notice.
- Before you use our Products, please contact our sales representative and verify the latest specifications.
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Poducts beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products are intended for use in general electronic equipment (i.e. AV/OA devices, communication, consumer systems, gaming/entertainment sets) as well as the applications indicated in this document.
- 7) The Products specified in this document are not designed to be radiation tolerant.
- 8) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, servers, solar cells, and power transmission systems.
- Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 10) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 11) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 12) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.
- 13) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 14) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

## ROHM Customer Support System

http://www.rohm.com/contact/

#### **General Precaution**

- 1. Before you use our Products, you are requested to carefully read this document and fully understand its contents. ROHM shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any ROHM's Products against warning, caution or note contained in this document.
- 2. All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using ROHM's Products, please confirm the latest information with a ROHM sales representative.
- 3. The information contained in this document is provided on an "as is" basis and ROHM does not warrant that all information contained in this document is accurate and/or error-free. ROHM shall not be in any way responsible or liable for any damages, expenses or losses incurred by you or third parties resulting from inaccuracy or errors of or concerning such information.

Notice – WE Rev.001